



PV5 DVU 540 Vacuum Unit Fitting Instructions



1



2



3



4



5

Fitting Vacuum Unit - DIAGRAMS 1, 2 & 3

- 1 Prise blanking caps (A) from machine cover to remove (if fitted) and replace with locking catches (C). Note that the catches must fitted with the arrow pointing inwards as shown - *DIAGRAM 1*
- 2 Sit vacuum unit on top of rotary machine, align locking keeper (C) with mating catch (B) and apply vertical pressure on vacuum unit assembly to secure.
- 3 Connect suction hose between vacuum unit and brush guard.
- 4 Connect vacuum cable plug into rotary machine socket on handle.

WARNING!

The socket outlet is for use with Premiere DVU 540 and DVU 590 dry vacuum accessories only.

CAUTION!

This machine is for dry use only and shall not be used or stored outdoors or in wet conditions.

To fit Skirt - DIAGRAM 4

- 1 Tilt machine backwards so that handle rests on floor and base of machine is exposed.
- 2 Offer up skirt and align with mating brush guard moulding.
- 3 Fit accessory in normal manner.
- 4 Place machine in upright position.
- 5 To remove skirt reverse fitting procedure.

To fit Paper Bags - DIAGRAM 5

- 1 Remove vacuum lid by sliding retaining catch in outward direction as shown.
- 2 Remove the paper bag from chrome location tube and discard.
- 3 Open out new paper bag, place in container and slide collar over chrome location tube.
- 4 Replace lid onto vacuum unit and push retaining catches inward to secure.

List of Parts:

1. DVU 540 Vacuum Unit
2. Locking Catch - 2-off